

Product data sheet

HEATING TYPE

Heating type	Induction
--------------	-----------

CONSTRUCTION TYPE

Independent of oven	•
---------------------	---

DESIGN

Elegant glass ceramic surface	•
Ceramic surface colour	Black
Stainless-steel frame	•
Surface-mounted installation	•

COOKING ZONE DETAILS

Number of cooking zones	5
Number of cooking areas	0
Maximum number of pans	5

USER CONVENIENCE

Operation via sensor controls	Smart Select
Display colour	Yellow
Pan and pan size recognition	•
Constant pan recognition	•

Recall function	•
Stop & Go function	•
Timer	•
Safety shut-off	•
Auto heat-up	•
Keeping warm	•
Individual setting options (e.g. audible signal tones)	•
Networking with Miele@home	•
Con@ctivity 3.0 automatic function	•

CLEANING CONVENIENCE

Easy-to-clean ceramic glass	•
------------------------------------	---

SAFETY

Safety shut-off	•
Safety lock	•
System lock	•
Integrated cooling fan	•
Overheating protection	•
Residual heat indicator	•

TECHNICAL DATA

Dimensions in mm (width)	36 1/8 (915)
Installation height incl. connection box in mm	2 7/8 (71)
Dimensions in mm (depth)	21 1/2 (544)

Cutout dimension in mm (width) with surface-mounted installation	34 1/2 (876)
-------------------------------------------------------------------------	--------------

Cutout dimensions in mm (depth) with surface-mounted installation	20 1/2 (518)
--------------------------------------------------------------------------	--------------

Weight in lbs (kg)	46 (21)
---------------------------	---------

Total rated load in kW	9.900-11.500
-------------------------------	--------------

Voltage in V	0
---------------------	---

Frequency in Hz	60
------------------------	----

Dimensions in mm (height)	3 1/8 (78)
----------------------------------	------------

ACCESSORIES SUPPLIED

Power cable	•
--------------------	---

1ST COOKING ZONE / COOKING AREA

Position	front left
-----------------	------------

Type	Dual-circuit ring
-------------	-------------------

Max. rating in W	1400
-------------------------	------

Max. booster rating in W	1700
---------------------------------	------

Size in mm	100-160 mm
-------------------	------------

Max. TwinBooster rating in W	2,200
-------------------------------------	-------

2ND COOKING ZONE / COOKING AREA

Position	rear left
-----------------	-----------

Type	Dual-circuit ring
-------------	-------------------

Max. rating in W	2300
-------------------------	------

Max. booster rating in W	3000
---------------------------------	------

Max. TwinBooster rating in W	3700
-------------------------------------	------

Size in mm

160-230 mm

3RD COOKING ZONE / COOKING AREA

Position	Centred
Type	Dual-circuit ring
Size in mm	180-280
Max. rating in W	2600
Max. booster rating in W	3000
Max. TwinBooster rating in W	3700

5TH COOKING ZONE / COOKING AREA

Position	front right
Type	Dual-circuit ring
Size in mm	Ø 140–190
Max. rating in W	1850
Max. booster rating in W	2500
Max. TwinBooster rating in W	3000

4TH COOKING ZONE / COOKING AREA

Position	rear right
Type	Dual-circuit ring
Size in mm	Ø 140–190
Max. rating in W	1850
Max. booster rating in W	2500
Max. TwinBooster rating in W	3000