Product data sheet

CONSTRUCTION TYPE	
Built-in appliance	•
Integrated appliance	•
Door hinging	Right convertible
Convertible hinging	•
DESIGN	
Lighting	BrilliantLight
Front colour	CleanTouch Steel
USER CONVENIENCE	
CONTROLS	
Eco mode	•
User interface	MasterSensor
Independent temperature regulation of fridge and freezer compartments	•
SuperCool	•
SuperFrost	•
Number of temperature zones	3
Sabbath mode	•
Holiday mode	•

10/19/23, 3:41 PM KF 2802 SF | Miele

FRIDGE / FRIDGE SECTION

SlidingShelf	•
Door rack for tins	1
Height-adjustable tempered glass shelves	1
Number of crisper drawers	2
Door rack for bottles	2
FREEZER / FREEZER SECTION	
Number of freezer baskets	2
EFFICIENCY AND SUSTAINABILITY	
Energy Star	•
SAFETY	
Overflow protection	•
Safety lock	•
Acoustic door alarm	•
Acoustic temperature alarm, freezer section	•
Optical door alarm	•
Optical temperature alarm	•
TECHNICAL DATA	
Replacing lamps	Customer Service
Number of phases	1

9/23, 3.41 FW	KF 2002 SF Wilele
Niche width in inches (mm), min.	30 (762)
Niche width in inches (mm), max.	30 (762)
Niche height in inches (mm), min.	84 1/8 (2134)
Niche height in inches (mm), max.	84 1/8 (2134)
Niche depth in mm	24 1/8 (610)
Appliance width in mm	29 7/8 (756)
Appliance height in mm	83 3/4 (2125)
Appliance depth in mm	24 (608)
Weight in lbs (kg)	448 (203.1)
Door hinge technology	Fixed door
Total usable capacity in I	15.96 (452) ft³ (I)
Current consumption in milliamps (mA)	4000
Voltage in V	110-120
Fuse rating in A	10
Frequency in Hz	60
Length of power cable in m	11 (3.5)

ACCESSORIES SUPPLIED

Active AirClean filter

APPLIANCE CATEGORY

Fridge / freezer

AVAILABLE DISPLAY LANGUAGES

Available display languages via Language Options

bahasa malaysia