

# 60" GAS RANGE - 6 BURNERS, INFRARED CHARBROILER AND INFRARED GRIDDLE



GR606CG



## FEATURES

6 dual-stacked burners plus 16,000 Btu charbroiler and 15,000 Btu griddle

Convection oven for faster, more consistent cooking

Infrared broiler inside oven sears quickly and evenly

Dual-stacked, sealed burners for higher highs, lower lows

Heavy-gauge stainless steel

Continuous cast-iron grates for easy movement of pots and pans

Enhanced views into oven

Rigorously tested in our U.S. manufacturing facilities for decades of use

Exceptional 24/7 support from our Customer Care team in Madison

Signature red infinite control knobs

Spark ignition system re-ignites if flame goes out

Adjustable legs for stability, plus rear casters

## ACCESSORIES

11" Cutting Board

Bake stone kit (stone, rack and peel)

Stainless steel, brass or chrome bezels

High altitude conversion kit

Full-extension easy glide oven rack

Cast iron S-grates and wok grate

Stainless steel kickplate

Signature red, black or stainless steel control knobs

Front leg covers

5" and 10" stainless steel risers, and 20" riser with shelf


Accessories available through an authorized Sub-Zero dealer.  
For local dealer information, visit [subzero-wolf.com/locator](http://subzero-wolf.com/locator).



## KNOB OPTIONS



## TOP CONFIGURATION




## RANGETOP SPECIFICATIONS

- 1 - 9,200 Btu Burner
- 5 - 15,000 Btu Burners
- 16,000 Btu Charbroiler
- 1 - 15,000 Btu (13,000 Btu LP) Griddle


**PRODUCT SPECIFICATIONS**

Model	GR606CG
Dimensions	60 1/8"W x 37"H x 28 3/8"D
Oven 1 Interior Dimensions	24"W x 18 5/8"H x 17"D
Oven 2 Interior Dimensions	24"W x 18 5/8"H x 17"D
Oven 1 Usable Capacity	2.9 cu. ft.
Oven 1 Overall Capacity	4.4 cu. ft.
Oven 2 Usable Capacity	2.9 cu. ft.
Oven 2 Overall Capacity	4.4 cu. ft.
Door Clearance	19 1/2"
Weight	950 lbs
Electrical Supply	110/120 VAC, 50/60 Hz
Electrical Service	15 amp dedicated circuit
Gas Supply	3/4" rigid pipe
Gas Inlet	1/2" NPT female
Receptacle	3-prong grounding-type


**ELECTRICAL**




**GAS**



**DIMENSIONS**



**STANDARD INSTALLATION**



*\*Without ventilation hood, 42" (1067) minimum clearance countertop to combustible materials, charbroiler requires non-combustible materials.  
NOTE: Shaded area above countertop indicates minimum clearance to combustible surfaces, combustible materials cannot be located within this area.  
For island installation, 12" (305) minimum clearance back of range to combustible rear wall above countertop.*