

UP60N



Colour range

Body



Blue grey - BG



Antique white - AW



White - WH



Blue - MB



Stainless steel - SS



Graphite matt - MG



Glossy black - BK



Burgundy red - BU



Emerald green - EG



Optional RAL - RA
+

Finishes

Knobs, handles, frames (optional)



Brass - G



Copper - P



Chrome - C



Burnished - B

Optional solid door version

optional +

Order code: add letter "Q" before the "N" letter

Noblesse frames

optional → p. 138

Available ovens

Electric oven

Primary oven:
UOV 80 M


Maximum input:
3.7 kW

Secondary oven:
UOV 60 M


Maximum input:
3.5 kW

Configurations

7 burners with fry top* and coup de feu



9 burners with fry top*



Electric oven

UP60FSNMP

Brass/Copper/Chrome/Burnished

UP60FNMP

Brass/Copper/Chrome/Burnished







Fuel requirements

Natural gas / Liquid propane
Voltage: 240 Volts
Amps: 30

Natural gas / Liquid propane
Voltage: 240 Volts
Amps: 30

**Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

 Coupe de Feu 5500 btu/h	 Double ring Dual burner 25000 btu/h / 900 btu/h	 Griddle 10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h	 Oval burner 10500 btu/h / 3100 btu/h	 Big burner 10500 btu/h / 2000 btu/h	 Small burner 7000 btu/h / 1400 btu/h
---	--	--	--	---	--

Complements & accessories

Hood

UAG60

Hood

UANB60

Ladle holder panel

AM4-150

Brass/Copper/Chrome/Burnished

Technical drawing & dimensions

