





600 CFM/14.0 SONES @ 0.10" SP.

Dimensions

Overall bottom projection - 235/8" Available widths: 36"

Hood Body

Brushed 430 stainless steel

Motor

3 speed, permanently split capacitor motor. Rated 120 volts, 60 hz.

Lighting

Two - GU10 base, MR16, 50 watt halogen lights.

Ducting Options

Vertical ducting: 6" round duct adapter complete with back draft damper ensuring quiet operation.

Ductless: Requiers charcoal filter (not included).

Blower Wheel

Dual inlet, electronically balanced polymetric centrifugal blower wheel, 53/4" width 59 paddles.

Mounting

Ceiling mounted with included mounting bracket. Install 24" to 30" from cooking surface.

Filters


Grease Filter: BCGF-01 (included). Charcoal Filter: BCCF-01 (not included).

Available Finishes

Stainless Steel.







EXPANDED PERFORMANCE											
		Stati	c Pressure	e (inches d	Sones	Fan Speed	Power				
	0	0.1	0.25	0.5	0.75	1.0	@ .1 SP	RPM	Watts	Amps	
Air Flow - CFM	603	600	594	578	557	531	14.0	2560	551.0	3.8	

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITT	ED BY	DATE	
FAN Number	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	



U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785

Fax: (610) 696-8048

Canada: 8 Edvac Drive Brampton, Ontario L6S 5P2 Tel: (905) 456-2033 • 800-250-8767

Fax: (905) 456-1015