

8.0 DALI V-16 F Subwoofer Technical Specifications

V-16 F	
Frequency range (in-room)	19 - 200 Hz ±3 dB (Line input) 19 - 500 Hz ±3 dB (LFE input)
Input impedance	9 kOhm
Maximum SPL	122 dB @ 1m
Crossover LP frequencies	40 - 200 Hz
Low frequency driver	1 × 16-inch long-throw
Low frequency diaphragm	Anodised aluminium with CSS technology
Enclosure type	Bass reflex
Bass Tuning Frequency	18 Hz
Connection Input(s)	2 × RCA unbalanced (Stereo, mono or LFE) 2 × XLR balanced (Stereo, mono or LFE)
Connection output(s)	1 × XLR balanced (Follower out)
Recommended placement	Floor / Flush-mount
Continuous amplifier output power	1500 W RMS
Maximum amplifier output power	2500 W Peak
Mains power rating	550 W
Standby consumption	≤ 0.5 W
Other features	Flush mount option Constant Group Delay mode Room Mode Attenuation mode Cinema/Music/Boost sound modes Closed box mode

V-16 F	
Dimensions (H × W × D)	570.5 × 520 × 560 mm 22.46 × 20.47 × 22.04 inches
Shipping dimensions (H × W × D)	730 × 660 × 710 mm 28.74 × 25.98 × 27.95 inches
Minimum flush-mount installation dimensions (H × W × D)	> 590 × 560 × 650 mm > 23.23 × 22.05 × 25.59 inches
Weight [kg/lb]	55 kg 121.25 lb
Shipping weight [kg/lb]	65 kg 143.30 lb
Finish	Black Ash
Accessories included	4 × Optional port plugs 1 × Mains power cable
Optional accessories	DALI Spike Set
Spike thread size	M10

All technical specifications are subject to change without notice.

