# 1/0 5

# Jamo

## 5.25" 2-WAY OUTDOOR SPEAKER



## **SPECIFICATIONS**

FREQUENCY RESPONSE	72Hz - 18kHz
POWER HANDLING	40W RMS / 80W Peak
NOMINAL IMPEDANCE	4 Ohm
SENSITIVITY	88dB
LOW FREQUENCY DRIVER	133mm (5.25") Aluminum HCC
HIGH FREQUENCY DRIVER	25mm (1") Aluminum Dome
HIGH FREQUENCY DRIVER ENCLOSURE MATERIAL	25mm (1") Aluminum Dome UV Resistant ABS
	, ,
ENCLOSURE MATERIAL	UV Resistant ABS
ENCLOSURE MATERIAL ENCLOSURE TYPE	UV Resistant ABS Sealed Enclosure

#### DESIGN + PERFORMANCE

The smooth lines, satin painted finish, and compact design of the I/O 5 allows it to blend seamlessly into even the most luxurious of outdoor living space, while the 5.25" long-throw aluminum HCC woofer and 1" aluminum tweeter provide detailed, dynamic, balanced sound.

#### EASY, ROBUST INSTALLATION

The new Jamo I/O series features an ultra durable powder coated steel C-bracket for simple, easy, and reliable installation in any outdoor environment.

#### ALL WEATHER DURABILITY

A powder coated grille mated to a UV-resistant, ABS cabinet provides the utmost in all-weather capability. The new Jamo I/O series is designed and built to offer great outdoor audio year in and year out.