

TURNTABLE

Type	Direct Drive
Turntable Speeds	33 1/3, 45 rpm
Motor Torque	1.6 kg/cm
Wow & Flutter	<0.1%
Turntable Platter	POM (Polyoxy methylene)
Diameter	305 mm

TONEARM

Type	One piece aluminium casting
Effective Length	238 mm
Overhang	17.2 mm
Effective mass	11 g

INTERNAL PHONO STAGE

Gain @ 1kHz	42dB
Nominal output (with CA cartridge)	250m Vrms
Equivalent input noise (A-Weighted)	0.1u Vrms
RIAA Curve Accuracy	+/- 0.3dB 30Hz-20kHz
Signal/Noise ratio (ref 1V out, 20-20K BW)	>90dB
THD+N 1kHz	0.0025%
Input Impedance	47k Ω
Input Capacitance	320pF

OUTPUTS

Audio Output	RCA line level
Bluetooth	SBC/aptX/aptX HD

GENERAL

Power Supply	AC 100-240V, 60/50Hz
Power Consumption	6W Approx., 20W max, <0.5W (Standby)
Dimensions (W x H x D)	435 x 139 x 368 mm
Weight	11 kg

CARTRIDGE

Type	High Output Moving Coil
Frequency response	+/- 1dB 30Hz-20kHz
Stylus	Elliptical
Cantilever	Aluminium
Output level	2mV @ 1kHz
Tracking force	2 g
Recommended load	47k Ω