AT-VM95ML/H Cartridge & Stylus

Frequency Response	20-25,000 Hz
Channel Separation	23 (dB at 1 kHz)
Vertical Tracking Angle	23°
Vertical Tracking Force	1.8-2.2 g (2.0 g standard)
Stylus Construction	Nude square shank
Recommended Load Impedance	47,000 ohms
Coil Impedance	3.3 k ohms (1 kHz)
DC Resistance	485 ohms
Coil Inductance	550 mH (1 kHz)
Output Voltage	3.5 mV (1 kHz, 5 cm/sec.)
Output Channel Balance	1.5 dB (1 kHz)
Stylus Shape	2.2 x 0.12 mil Microlinear
Cantilever	Aluminum pipe
Static Compliance	20 x 10 – 6 cm / dyne
Dynamic Compliance	10 x 10 – 6 cm / dyne (100 Hz)
Mounting	Half-inch
Dimensions	Cartridge 17.2 mm (0.68") H × 18.9 mm (0.74") W × 28.3 mm (1.20") D; Cartridge & Headshell 21.2 mm (0.83") H × 21.4 mm (0.84") W × 62.4 mm (2.46") D
Accessories Included	Two 11 mm installation screws, two 8 mm installation screws, two washers, nonmagnetic screwdriver
Model	AT-VM95ML/H
Mounting Feature	Half-inch mount
Recommended Load Capacitance	100 to 200 pF
Replacement Stylus	AT-VMN95ML
Stylus Size	2.2 x 0.12 mil
Type	VM Stereo Dual Magnet
Weight	Cartridge 6.1 g (0.22 oz); Cartridge & Headshell 15.5 g (0.55 oz)
Wire Used for Coil	T.P. Copper