

The PM300SS built-in powerpack insert offers you a custom appearance while protecting cabinetry with stainless steel liners. Featuring a smooth, stainless steel surface that is easy to clean with quick-release dishwasher-safe filter. The bright LED lighting enhances your cooking experience.

SIZE	STAINLESS	GREASE FILTER (replacement)	NON-DUCTED FILTER
21-3/8 in.	PM300SS	S99100628-121 (Aluminum)	S99010464 (Charcoal)

HVI PERFORMANCE							
		Damper	Sones		CFM		
Duct Orientation	Size		Normal	High	Normal	High 0.25 in. w.g.	High 0.1 in. w.g.
Round - Vertical	7 in.	Not included	3.0	7.0	140	115	260

FEATURES	
Max. Blower CFM*	300
Control type	2-Speed Rocker Switch
Delay off	no
Filter Clean Reminder	no
Heat Sentry™	no
ADA Capable	yes
Lighting	1-level LED (2 LED modules included)
Grease Filter	Micromesh (Qty. 1)
Installation Hardware	Included
ENERGY STAR®	no
Recirculation	Non-ducted kit sold separately
AC INPUT	

120 V, 60 Hz - 2.3 AMPS				
	120 V,	60 Hz -	2.3	AMPS

OPTIONAL ACCESSORIES		
Stainless Steel Liners	LB30SS, LB36SS	
ADA Kit	HAWSK3	
Non Duct Kit	HARKPM21	
Power Cord Kit	HCK44 (U.S.A. only)	
Damper	BP87Q	
Make-up Air Dampers	MD6TU, MD8TU and MD10TU	


MOUNTING HEIGHT

24 in. to 30 in. from cooktop to bottom of hood


LIMITED WARRANTY

1-year

FOR INDOOR USE ONLY







Dimensions shown in inches.

Can be used to comply with LEED requirements.

HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 and 0.25 in. static pressure at high speed based on tests conducted in an HVI-approved state-of-the-art test laboratory. Sones are a measure of humanlyperceived loudness, based on laboratory measurements.

1105851A

^{*} Max. blower CFM indicates the performance of the hood blower in open air.