




7085 Basillica

	US Units	Metric Units
Style Number	703SA	
Construction	SPC	
Profile	Fold-N-Tap	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.217"	5.5 mm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Attached Underlayment	EVA Pad	
Attached Underlayment Thickness	0.059"	1.5 mm
Finish	ScuffResist	
Edge Description	Accent Bevel	
Area per Carton	18.91 sq ft	1.76 sq m
Area per Pallet	1512.8 sq ft	140.54 sq m
Installation	Floating	
Installation Grade	Above, On, Below	
Ortho-Phthalates Free	Yes	
Embossed In Register	Yes	
FloorScore Certified	Yes	
Residential Warranty	Lifetime	
	Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof	
Commercial Warranty	10 Year Light Commercial	
Smoke Density (ASTM E662, Flaming Mode)	Passes, <450	
Radiant Panel (ASTM E648)	Passes, Class I	

Colors



Coordinating Trim



Baby Threshold*

BT3HS | 94"


VSBTB | 94"



T-Molding*

TM3HS | 94"

VSTM6 | 94"



Multi-Purpose Reducer

VSMP6 | 94"



Quarter Round

VSQT6 | 94"



Flush Stairnose

VFSN1 | 94"

*Packaged with molding track

Coordinating Metal Trim



Reducer



T-Mold



Stair Cap

Finish

Satin Silver

143SA

146SA

140SA

Satin Nickel

144SA

147SA

141SA

Dark Bronze

145SA

148SA

142SA

Installation Range

Profile Size

3.5mm

Installation Range

1.5mm to 3.5mm heights

5.5mm

3.6mm to 5.5mm heights

8mm

6mm to 8mm heights



g Stair Treads

Stair Tread TRIHS

White Riser LVWRI*

*packages of 3