

Broan brings you Spire, an exciting new shape in a pro-style hood. The new design incorporates modern features like the quiet Captur™ system and LED lighting.

SIZE	STAINLESS	GREASE FILTERS (replacement)	NON-DUCTED FILTERS
30 in.	BPDP130SS	HPFA424 (Type "B5")	HPF24 (Type "Xb")
36 in.	BPDP136SS	HPFA430 (Type "C5")	HPF30 (Type "Xc")
42 in.	BPDP142SS	HPFA436 (Type "D5")	HPF36 (Type "Xd")
48 in.	BPDP148SS	HPFA442 (Type "E5")	HPF42 (Type "Xe")

PERFORMANCE							
Decet Orientation	Size	Damper	Sones		CFM		
Duct Orientation			Normal	High	Normal	High	
Vertical - Rectangular	3¼ in. x 10 in.	Included	0.3	6.5	120	360	
Horizontal - Rectangular	3¼ in. x 10 in.	Included	0.3	6.5	120	400	
Round - Vertical	7 in.	Sold Separately	0.5	6.5	120	370	

FEATURES				
Control type	2-speed Deluxe Rocker			
Delay off	no			
Filter Clean Reminder	no			
Heat Sentry™	no			
ADA Capable	yes			
Lighting	1-level LED (included)			
Grease Filters	Hybrid Baffle (Oty. 2)			
Installation Hardware	EZ1 brackets			
ENERGY STAR®	no			
Recirculation	Non-ducted filters sold separately			

AC INPUT

120 V, 60 Hz - 1.4 AMPS

OPTIONAL ACCESSORIES				
7-in. Round Damper	BP87Q			
ADA Wiring Kit	HAWRK3			
Make-up Air Dampers	MD6TU, MD8TU and MD10TU			

MOUNTING HEIGHT

18 in. to 30 in. from cooktop to bottom of hood


LIMITED WARRANTY

1-year


3-year (LED modules only)

(See installation manual for full warranty text.)

FOR INDOOR USE ONLY









SPECIFICATION SHEET



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-ofthe-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.