

COMMERCIAL  
THROUGH RETAIL

PREP FOR CARD  
FRONT LOAD  
WASHERS  
AND TOP LOAD  
WASHERS



Product	Front Load Washer	
	Rear Control	Front Control
Color	White	
Capacity - lb (kg)	21.5 (9.5)	
Cylinder Volume - cu.ft. (liters)	3.42 (96.8)	
Spin Speed G-Force (RPM)	440 (1200)	
Motor Size - HP (kw)	0.9 (0.67)	
Water Consumption Per Cycle - g (liter)*	13.68 (51.8)	
IWF (Water Factor) - gal/ft³ (liters/liter/cycle)*	4.0 (0.53)	
MEF <sub>32</sub> (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)*	2.20 (62.3)	
Available Water Temperatures	Cold, Warm, Hot	
Available Cycles	Normal, Synthetic, Delicate	
Electrical Requirements (v/Hz/Ph-Amp)	120/60/1-15 Amp	
Water Pressure - p.s.i (bar)	20-120 (1.4/8.3)	
Drain	Pump	
Cylinder Finish	Stainless Steel	
Net Weight - lb (kg)	260 (118)	
Shipping Weight - lb (kg)	270 (122.2)	
Shipping Dimensions Approx. - in	Width	34
	Depth	30
	Height	44.5
Agency Approvals	cULus, ENERGY STAR® certified	
Model No.	SFNNYRSP116TW01	SFNNYASP116TW01

Product		Top Load Washer
Color		White
Capacity - lb (kg)		16 (7.3)
Cylinder Volume - cu.ft. (liters)		3.19 (90.3)
Spin Speed G-Force (RPM)		150 (710)
Motor Size - HP (kw)		0.5 (0.37)
Water Consumption Per Cycle - g (liter)*		28.07 (106)
IWF (Water Factor) - gal/ft³ (liters/liter/cycle)*		8.8 (1.18)
MEF <sub>32</sub> (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)*		1.35 (38.2)
Available Water Temperatures		Cold, Warm, Hot
Available Cycles		Normal, Synthetic, Delicate
Electrical Requirements (v/Hz/Ph-Amp)		120/60/1-15 Amp
Water Pressure - p.s.i (bar)		20-120 (1.4/8.3)
Drain		Pump
Cylinder Finish		Stainless Steel
Net Weight - lb (kg)		206 (93.4)
Shipping Weight - lb (kg)		218 (98.8)
Shipping Dimensions Approx. - in	Width	28
	Depth	30
	Height	45
Agency Approvals		cULus
Model No.		SWNNY2SP116TW01

Dimensions	Width - in	Height - in	Depth - in	Floor to Door Opening - in	Door Swing - in
Front Load Washer - Rear Control	26.875	43.875	27.73	14.6	24
Front Load Washer - Front Control	26.875	44.34	27.73	14.6**	24
Top Load Washer	25.625	43	28	51	–

For Commercial Use Only

Supply inject kits available.

\* Average usage based on multiple load sizes and current DOE test protocol.  
Real usage will vary depending on load size, composition and cycle selectivity.

\*\* For ADA compliance turn legs out from base 0.5 inches

For additional accessories and warranty, please refer to the price list.