

## SPECIFICATIONS

### INPUTS

Inputs: 7 RCA Unbalanced, 7 XLR Balanced  
Input Sensitivity: 1.42 Vrms for full output  
Maximum Input Voltage: 2.7 Vrms  
Input Impedance: 100 k $\Omega$

### OUTPUTS

Amplifier Channels: 7  
Power Output (8 $\Omega$ ): 230 watts per channel  
Power Output (4 $\Omega$ ): 300 watts per channel  
Power Output (8 $\Omega$  Bridged Mono): 600 watts  
Minimum Speaker Load: 4 $\Omega$

### PERFORMANCE

Damping Factor: >450  
Total Harmonic Distortion: 0.04% (230 watts @ 8 ohms 20 Hz-20 kHz)  
Signal to Noise: >102dB, A-wtd ref Full Output  
Frequency Response: 10 Hz -20 kHz,  $\pm 1$  dB

### CONTROL

Remote Power Trigger: +12 VDC or Dry Contact Closure

### GENERAL

Power Consumption (Standby): < 2W  
Power Consumption (Idle): 38W  
Power Consumption (loud listening level): 367W  
Power Consumption (maximum): 2100W  
BTU/Hour Output (Standby): 5.6 BTU/hr  
BTU/Hour Output (Idle): 129 BTU/hr  
BTU/Hour Output (1/8th power, loud listening level): 477 BTU/hr  
BTU/Hour Output (maximum): 2507 BTU/hr  
Protection: clipping, short circuit, thermal, DC offset

### WEIGHTS & DIMENSIONS

Dimensions: 17"W x 16.5"D x 5.25"H (3U)  
Weight: 43.0 lbs (19.5 kg)

**IN THE BOX:** Savoy G4, Power Cord, Manual, Warranty