Specifications

Digital Output	COAXIAL, OPTICAL & AES/EBU	PCM 16-24Bit /44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz DSD 2.8MHz (DoP)
	IIS LVDS	PCM 16-32Bit /44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz, 352.8kHz, 384kHz, 705.6kHz, 768kHz DSD 2.82MHz, 3.07MHz, 5.64MHz, 6.14MHz, 11.29MHz, 12.29MHz, 22.58MHz, 24.58MHz
	USB DAC	Depends on the specifications supported by the connected USB DAC device. Not higher than PCM 32Bit/768kHz and DSD 24.58MHz. The USB DAC port provides a maximum of 5V/1A low-noise power supply.
Network	LAN	10/100/1000 Mbps
	Wi-Fi	2.4 GHz / 5 GHz
USB	USB 3.0 * 2	The USB port provides a maximum power of 5V/1A. The USB port works with devices which conform to the USB mass storage standard and supports FAT, FAT32, exFAT, and NTFS file formats, but is not guaranteed to be compatible with all storage devices.
Trigger	Trigger in	DC 6-12V<10mA
	Trigger out	DC 12V/50mA MAX
MA Player	Controller app	MA Remote App
	Local Playback	Format Supported: MP3 , WMA , WAV , AIF, AIFC, AIFF, AAC, FLAC, OGG, APE, ALAC, M4A, DSF, DFF, CUE、ISO PCM 16-24Bit/44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz, 352.8kHz, 384kHz, 705.6kHz, 768kHz DSD 2.82MHz, 3.07MHz, 5.64MHz, 6.14MHz, 11.29MHz, 12.29MHz, 22.58MHz, 24.58MHz
	Roon Ready	PCM 16-24 Bit /44.1 kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz, 352.8kHz, 384kHz, 705.6kHz, 768kHz DSD 2.82MHz, 5.64MHz, 11.29MHz, 22.58MHz
	QQMusic	The audio specs depend on the service provider
	AirPlay 2	The audio specs depend on the service provider
	DLNA/UPnP	The audio specs depend on the service provider
	TIDAL Connect	The audio specs depend on the service provider
	Spotify Connect	The audio specs depend on the service provider
	Qobuz Connect	The audio specs depend on the service provider
	vTuner	The audio specs depend on the service provider
	Radio Paradise	The audio specs depend on the service provider
Storage Extension		M.2 2280 2260 2242 NVMe PCIe SSD slot *1 The maximum power specification provided by the expansion slot is DC 3.3V/3A.
Power Specs	AC Input	Wide voltage switching power supply Power Voltage: AC 100V-240V 50/60Hz Power Consumption: < 35W

	DC Input	External power voltage: DC 12V ±10% External power wattage: Larger than 35W Power plug: Outer diameter 5.5mm; inner diameter 2.1mm (+ for inner, - for outer)
Weight & Size	Weight	2.76kg (6.08 pounds)
	Size	Width: 280 mm (11.02 inches) Depth: 210 mm (8.27 inches) Height: 82 mm (3.23 inches)
Accessories		Power cable *1 Printed material *1