

Specifications

The specifications of this unit are as follows.

Output Jacks

- Analog audio x 1 (RCA Unbalanced)
- Digital audio
OPTICAL x 1

Other jacks

- USB × 1 (USB2.0)
- REMOTE IN × 1
- REMOTE OUT × 1

* The contents of this manual apply to the latest specifications as of the publishing date.
To obtain the latest manual, access the Yamaha website then download the manual file.

Audio Section

- Output Level (1 kHz, 0 dB, Fs 44.1 kHz).....2.0±0.3 V
- S/N Ratio (IHF-A Network) (1 kHz, 0 dB, Fs 44.1 kHz) 105 dB or higher
- Dynamic Range (1 kHz, 0 dB, Fs 44.1 kHz) 96 dB or higher
- Harmonic Distortion (1 kHz, 0 dB, Fs 44.1 kHz) 0.003% or lower
- Frequency Response
 - Audio CD 2 Hz – 20 kHz
 - Data CD/USB
 - Fs 48 kHz..... 2 Hz – 22 kHz
 - Fs 96 kHz..... 2 Hz – 44 kHz, –3 dB

Laser section

- Laser Type AlGaAs
- Wavelength 790 nm
- Laser Output Max. 2.15 μ W

* This output is the value measured at a distance of about 100 mm from the objective lens surface on the Optical Pick-up Block.

General

- Power Supply
 - U.S.A. and Canada modelsAC 120 V, 60 Hz
 - Australia modelAC 230-240 V, 50 Hz
 - Europe and U.K. modelsAC 230 V, 50 Hz
 - Asia and General modelsAC 110-240 V, 50/60 Hz
- Power Consumption 11 W
- Standby Power Consumption
 - Power Standby 0.2 W
 - Power Off 0.2 W
- Dimensions (W × H × D)435 × 116 × 405 mm
 (17-1/8" × 4-5/8" × 16")
- Weight 5.6 kg
 (12.3 lb)