## accuc@ld

# ARS1PV456



21.5" x 17.5" x 19.75" (H x W x D)

Performance series Pharma-Vac 1 cu.ft. all-refrigerator certified to NSF/ANSI 456 Vaccine Storage Standard

### **Highlights:**

Certified to NSF/ANSI 456 Vaccine Storage Standard

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

#### **Product Features:**


Certified to NSF/ANSI 456 Vaccine Storage Standard	Designed and tested to comply with the new NSF Vaccine Storage Standard
Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Certificate of calibration included	2-year calibration certificate included for your records
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce germ spread
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup



## accuc@ld

### **ARS1PV456 Specifications:**

Overview	
Height of Cabinet	21.5" (55 cm)
Width	17.5" (44 cm)
Width with Door Open	18.0" (46 cm)
Depth	19.75" (50 cm)
Depth with Handle	21.5" (55 cm)
Depth with door at 90°	36.0" (91 cm)
Capacity	1.0 cu.ft. (28 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S to NSF 456
Amps	0.6
Voltage/Frequency	115 V AC/60 Hz
Weight	61.0 lbs. (28 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101090696
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	3
Adimetable Objectives	
Adjustable Shelves	Yes
Adjustable Shelves Thermostat Type	
<del>-</del>	Digital
Thermostat Type	Digital Interior
Thermostat Type Fan Type	Digital Interior R600a
Thermostat Type Fan Type Refrigerant Type	Digital Interior R600a 0.71oz.
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount	Digital Interior R600a 0.71oz. Yes
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light	Digital Interior R600a 0.71oz. Yes 2 to 8°C
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range	Digital Interior R600a 0.71oz. Yes 2 to 8°C
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Sound Level	Digital Interior R600a 0.71oz. Yes 2 to 8°C 39 dB
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Sound Level Dimensions	Yes  Digital Interior R600a 0.71oz. Yes 2 to 8°C 39 dB  15.75" (40 cm) 14.0" (36 cm)
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Sound Level Dimensions Interior Height	Digital Interior R600a 0.71oz. Yes 2 to 8°C 39 dB





ELEC. CORD