

LUMINA NRS

Version

FNLUM36W5SS / Wall - 36"
(90 cm) Steel - 500 CFM

Collection

Silence - NRS

EAN code

8034122345888

FEATURES

NRS technology for a quieter kitchen
Touch control + 24 h function
White fluorescent ambient light
Metallic grease filter, removable and washable
Optional charcoal filter

Recommended mounting height from cooking surface to hood bottom: 24" - 35";
 Availability Carbon.Zeo filter KACL.961/ for hoods produced from 10/22/2020

OPTIONAL ACCESSORIES

KACL.400

Silent / Conveyor NRS

KACL.570#I

Extension H700 - Wall

KACL.571#I

Extension H960 - Wall

KACL.815

Protective cleaning cloths for stainless steel (box 10 pcs)

KACL.961

Charcoal and Zeolite filter

101078900

High performance filter

TECHNICAL FEATURES

Installation type

Wall

Dimensions

36 / 90 cm

Finish

Scotch brite stainless steel (AISI 304)

Tempered glass with white finish

Motor

500 CFM

Type of control

Touch control

Speed settings

4

Lighting

Fluorescent 1x21 W

Filter

2 x Metallic filter "Base" - 274x274 mm

Charcoal filter

High performance filter (optional)

Minimum distance

Gas hob: 26 in

Electric hob: 21 in

PACKAGING:WEIGHTS AND VOLUMES

Gross weight

93 lbs

Net weight

80 lbs

Volumes

19 ft³

Packaging size

Length

41 in

Height

27 in

Depth

30 in

CONSUMPTION AND CONNECTION FEATURES

Maximum consumption

340 W

Plug type

Hood comes standard with Nema 5-15P power cord

MOTOR TECHNICAL SHEET

Maximum capacity

610 m³/h

I.E.C. 61591

Maximum noise level

55 dB(A)re1pW


I.E.C.60704-2-13

Maximum pressure (Pa)

582 Pa

Max. motor power

224 W



LUMINA NRS

Version

FNLUM36W5SS / Wall - 36"
(90 cm) Steel - 500 CFM

Collection

Silence - NRS

EAN code

8034122345888

MOTOR TECHNICAL SHEET

Motor Speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	37	41	46	55
Capacity (m3/h) I.E.C.61591	190	300	380	610
Maximum pressure (Pa)	490	500	520	582
Motor Power (W)	130	150	178	224
Air outlet	150	150	150	150

CAPACITY / PRESSURE

