

K-CKTPD2-BI Built-in Double Cooktop



PRODUCT FEATURES

- Dual 19,000 BTU cooktop burners
- Natural gas or bulk propane
- Continuous stainless steel grate
- Battery powered electronic ignition
- For masonry installation or with a 24" Kalamazoo base cabinet, available in Signature and Arcadia Cabinet Series
- Stainless steel cover included
- Marine-grade stainless steel available

Overall Width / Installation Width	16 in (407 mm)
Overall Depth / Installation Depth	28.38 in (720 mm)
Overall Height / Counter Height	7 in (179 mm)
Approximate Product Weight	34 lb (15.4 kg)
Gas Requirements	Natural Gas: 3/8" (10 mm) male NPT connection. 12 ft. (366 cm) gas hose with
	external regulator and quick disconnect provided. Gas service line to deliver 7 i.w.c.
	at grill location. See BTU information below for pipe sizing.
	Bulk Propane: 3/8" (10 mm) male NPT connection. 12 ft. (366 cm) gas hose with
	external regulator and quick disconnect provided. Gas service line to deliver 11 i.w.c.
	at grill location. See BTU information below for pipe sizing.
	Propane Cylinder: Not available
Electrical Requirements	1.5V "AAA" battery x 1
Total BTUs	38,000 BTU propane / 33,000 BTU NG

Ensure proper gas pipe sizing. Diameter and length of the supply pipe may limit the pressure and BTU delivery.

For outdoor use only. Maintain at least 9 inches (229 mm) of clearance around the sides and back of cooktop. Never place cooktop underneath an overhead combustible surface. For installation in built-in enclosure constructed of non-combustible materials. Do not place cooktop in a location where it is likely to be exposed to a strong wind.

High altitude kit available.



8566 KRUM AVENUE GALESBURG, MI 49053 KALAMAZOOGOURMET.COM +1.800.868.1699

K-CKTPD2-Bl Built-in Double Cooktop

