KLIPSCH PSM-450-T

FULL-RANGE 4.5" INDOOR/OUTDOOR PROFESSIONAL SURFACE MOUNT LOUDSPEAKER



MORE BASS, LESS SPACE WITH THE ALL-NEW TRACTRIX® HYPERFOLD PORT™
Klipsch is all about high efficiency, low distortion. Building upon that legacy, we're introducing the all-new patented Tractrix® Hyperfold Port™ engineered to extend port length for maximum bass power via proprietary five-step folded design. Its increased airflow eliminates chuffing and port noise while providing a greater dispersion pattern for larger coverage areas.

IPX6 RATED FOR COMMERCIAL ENVIRONMENTS
Perfect for indoor and outdoor commercial installations around the globe, the Klipsch PSM-450-T is IPX6 Rated. Your clients will rest easy knowing their new speakers will be water-resistant and rainproof for the most challenging commercial environments.

MULTIPLE TAP SETTINGS
The PSM-450-T includes a multi-tap transformer for 70 or 100 volt installations. There is also a bypass position that allows normal 8 ohm operation for installations that do not require a transformer.

SET SCREWS ON GRILLE
The included set screws on each grille ensures a secure fit between the speaker and grille , while making sure the grilles stay on the enclosures regardless of the environment.

1" TITANIUM COMPRESSION DRIVER FOR EFFORTLESS, HIGH-CLARITY DETAIL
Klipsch outperforms the competition with our all-new 1" Titanium-loaded floating driver bridge with wide dispersion phase plug. Using our patented mumps technology, the PSM-450-T gives any space extra-wide coverage while providing even and consistent energy for your project.

PHOENIX CONNECTOR FOR SIMPLIFIED INSTALLATION
The PSM-450-T employ a phoenix connector for quick and intuitive connection.

SPECIFICATIONS

FREQUENCY RESPONSE[1]	60Hz-20kHz +/- 4dB, 50Hz -10dB
POWER HANDLING[2]	50 watts (14.6V) 58Hz-10kHz (200 watts peak)
CALC. MAX. CONT. OUTPUT[3]	102dB
SENSITIVITY[4]	88dB
COVERAGE	90° +/- 40° 1kHz-20kHz
DIRECTIVITY INDEX	7dB +/- 3dB 800Hz-20kHz
NOMINAL IMPEDANCE	8 ohms 4.3 ohms at 185Hz minimum
ACOUSTIC CROSSOVER	2kHz
TRANSDUCERS	4.5" woofer 1" titanium compression driver, on a K-1500M horn/tweeter bridge
ENCLOSURE MATERIAL	All Weather ABS Plastic, Paintable
IP RATING	IPX6
ENCLOSURE TUNING	Vented via 3 folded Tractrix ports
INPUT CONNECTORS	4 pin euro block
TRANSFORMER TAPS	70V: 15W, 7.5W, 3.8W, 1.9W 100V: 15W, 7.5W, 3.8W Bypass position: 8 ohms nominal
DIMENSIONS [WITH BRACKET]	12.13"(309mm) x 9.5"(242mm) x 6.5"(166mm) [8.38"(213mm)]
WEIGHT	7.25 lbs (3.29kg)

[1] 1m, half space, anechoic
[2] AES standard, continuous pink noise 50hz-10kHz, 6dB peaks
[3] Calculated at 1m at power handling power input
[4] SPL at 1m half space, anechoic with 2.83V pink noise input

CE
EN54-24

RoHS COMPLIANT

All specifications are subject to change without notice. ©2023 Premium Audio Company, LLC, a wholly-owned subsidiary of Voxx International Corporation. Klipsch Group, Inc. is a wholly owned subsidiary of Voxx International Corporation. Klipsch is a trademark registered in the USA and other countries, and is owned by Klipsch Group, Inc.