



Color Variants

BM281710
Stainless steel
Left-hinged

BM281730
Aluminium
Left-hinged

Included accessories

1 x grid.

BM281710

200 series microwave oven

Stainless steel

Left-hinged

- 200 Series built-in microwave oven
- For installation into tall cabinets
- Net volume 2.1 cu.ft.
- Oven interior dimensions: W 18 7/16" x H 10 15/16" x D 18 1/2" (469 x 278 x 470 mm).
- 20 automatic programs with cook-by-weight settings:
 - 3 defrosting programs
 - 6 cooking programs
 - 9 combination programs
 - 2 reheating programs.

Operation

Digital function display.
Adjustable cooking time up to 90 minutes.
Easy operation with sensor touch keys.
Microwave and heating modes can be combined or selected separately.

Features

Innowave - variable power settings.
16 1/2" glass rotating plate.
Stainless steel interior.
10 power levels.
Super-Quick preheating.
Kitchen timer.
20 W interior light.
Side-opening door with panoramic window.

Safety

Child lock.
Push release door opening system.
Triple door lock.

Planning notes

Door hinge not reversible.
Minimum installation height 36 1/16".
When using BA 268, the front of the appliance extends 1 7/8" from the cabinet front.
For integration into the housing of lift door BF 283 or the built-in trim kit with BA 268, matching the 200 oven series. The front of the appliance extends 1 7/8" from the cabinet front.
Plan intermediate shelf of at least 3/4".
Connecting cable 41" (1.0 m) with plug.

Rating

Total connected load 1.46 kW.
Total Amps: 20 A
120 V / 60 Hz

Product Features

Max. Microwave power (W)

1200

Number of Power Levels

10

Turntable

Yes

Turntable diameter (in)

16 9/16 "

Heating type

Microwave

Cavity material

Lacquered

Door opening

Button

Clock / Timer

Yes

Max. extraction rate (CFM)

Maximum output recirculating air

Ventilation Power Levels

Type of Filter

Type of lights

Number of lights

Included accessories

1 x grid

Consumption and connection features

UPC code

825225853343

Product color

Stainless steel

Alternative colors available

BM281730

Watts (W)

1460

Current (A)

20

Volts (V)

120

Frequency (Hz)

60

Approval certificates

CSA, UL

Power cord length (in)

41 "

Plug type

120V-3 prong

Required cutout size (HxWxD) (in)

x x

Overall appliance dimensions (HxWxD)

(in)

14 " x 23 7/8 " x 19 7/16 "

Product packaging dimensions

(HxWxD) (in)

18.89 x 18.11 x 26.37

Net weight (lbs)

34

Gross weight (lbs)

40

2013-07-02

Page 1

