## PODS302W 30-INCH DOUBLE COMBINATION BUILT-IN OVEN WITH STEAM CONVECTION PROFESSIONAL SERIES





Home Connect

### FEATURES & BENEFITS

- Specially crafted gray glass on stainless steel for a luxurious look and finish
- Designed for flexibility—standard or flush installation into kitchen cabinets
- Steam and Convection Cooking provides unrivaled taste and quality—food stays moist on the inside and is perfect on the outside
- Steam and Convection Oven offers passionate cooks more cooking solutions Broil, Steam, True Convection, Steam and Convection
- Large commercial style rotisserie with 12 pound capacity

### ACCESSORIES (INCLUDED)

....

Upper Cavity: 3 Telescopic Racks, Multi-point Meat Probe, Broil Pan, 1 Large Perforated Pan, 1 Small Pan, 1 Small Perforated Pan; Lower Cavity: 3 Telescopic Racks, Multi-point Meat Probe, Max Broil Pan, Rotisserie

WARRANTY	
Limited Warranty Parts and Labor	2 Year

### GENERAL PROPERTIES

Heating Modes - Upper Cavity

(17) Bake, Broil, Roast, Convection Bake, Convection Broil, Convection Roast, Steam Convection, Defrost, Proof, Warm, Pizza, True Convection, Dehydrate, Speed Convection, Slow Roast, Steam, Reheat, Steam Auto Programs

Heating Modes – Lower Cavity

(16) Bake, Broil, Max Broil, Roast, Convection Bake, Convection Broil, Max Convection Broil, Convection Roast, Proof, Warm, Pizza, True Convection, Dehydrate, Speed Convection, Slow Roast, Rotisserie

Sabbath		Yes
Cleaning Type	Upper Cavity Lower Cavity	Easy Clean, Ecolytic Clean Easy Clean and Self Clean
Telescopic Rack(s)		6
Illumination Type	Upper Cavity Lower Cavity	LED Halogen
Interior Lights	Upper Cavity Lower Cavity	3 – 1 Top, 2-Sides 2 – Sides with 2 Bulbs Each
Home Connect® (Wi-Fi Enabled)		Yes, Upper & Lower
OVEN PERFORMANC	E	
Bake / Broil Element	Upper Cavity Lower Cavity	1,420 W / 3,050 W 2,400 / 1,000 / 3,800 W
Convection Element	Upper Cavity Lower Cavity	2,300 W 2,000 W
TECHNICAL DETAILS		
Watts		9,200 W
Circuit Breaker		40 A
Volts; Frequency		240 / 208 V; 60 Hz
Plug Type		Fixed Connection, No Plug
Conduit		60" 4-Wire
Energy Source		Electric
DIMENSIONS & WEIG	ынт	
Overall Appliance Dimensions (HxWxD)		48 <b>7</b> /8" 29 <b>3</b> /4" × 24 <b>1</b> /2"
Trim Overlaps (Top – Sides – Bottom)		<b>3/4</b> " to 1 <b>1/2</b> " - <b>9/16</b> " - 0"
Required Cutout Size (HxWxD) – Standard		47 3/8"- 48 1/8" x 28 1/2" x 23 1/2"
Required Cutout Size (HxV	VxD) – Flush	49" x 30" x 24 <b>1</b> /2"
Steam Convection Oven C	Capacity	2.8 cu. ft.
Oven Capacity		4.5 cu. ft.
Overall Oven Interior Dime	ensions (HxWxD) Upper Cavity Lower Cavity	14 1/2" × 18 7/8" × 17 3/8" 17 3/4" × 24" × 17 7/8"
	Upper Cavity Lower Cavity	

# PODS302W 30-INCH DOUBLE COMBINATION BUILT-IN OVEN WITH STEAM CONVECTION PROFESSIONAL SERIES



### **30-INCH DOUBLE COMBINATION OVEN**



\_\_24<sup>1</sup>/2"\_\_ (622 mm)

measurements in inches (mm)

## PODS302W 30-INCH DOUBLE COMBINATION BUILT-IN OVEN WITH STEAM CONVECTION PROFESSIONAL SERIES



#### INSTALLATION DETAILS



Double or combo oven over storage or warming drawer



These warranties give you specific legal rights and you may have other rights that vary from state to state. Limited warranty from date of delivery. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.

1 800 735 4328 | USA THERMADOR.COM | CANADA THERMADOR.CA | ©2023 BSH HOME APPLIANCES CORPORATION. ALL RIGHTS RESERVED.