DMC-S20-HD



2-Channel DigitalMedia 8G[™] Single-Mode Fiber Output Card for DM[®] Switchers

- > Modular output card for a DM-MD8X8, DM-MD16X16, or DM-MD32X32 switcher
- > Provides two independent DM 8G® Single-Mode Fiber outputs
- > Supports cable lengths up to 7.5 miles (12 km) using CresFiber® 8G SM or G.652.D single-mode fiber^[1]
- > Includes a parallel HDMI® port on the first output
- > Handles video resolutions up to Full HD 1080p
- > Handles computer resolutions up to UXGA and WUXGA
- > Handles 3D video and Deep Color
- > Handles Dolby® TrueHD, DTS-HD®, and uncompressed 7.1 linear PCM audio
- > HDCP compliant
- > Occupies a single output card slot

The DMC-S20-HD is an output card designed for use with any card-based Crestron® DigitalMedia™ Switcher. It provides two independent DM 8G® SM Fiber outputs, plus one HDMI® output. The HDMI output carries the same signal as the first DM 8G SM Fiber output. Each DM 8G SM Fiber output enables connection to a DM 8G SM Fiber Receiver, or the input of another DM® switcher. Using a single strand of single-mode fiber. [1]

All outputs on the DMC-S20-HD are capable of handling video resolutions up to Full HD 1080p, as well as computer resolutions up to WUXGA. DM 8G SM Fiber transports uncompressed high-definition video and computer signals over distances up to 7.5 miles (12 km) using CresFiber® 8G SM or G.652.D single-mode fiber optic cable.[1]

To configure a DM switcher complete with input and output cards, cables, and other peripherals, please use the online DigitalMedia Switcher Configuration Tool.

Are you upgrading an existing DM switcher that has older "multi-gang" DMCO-series output cards? Use the online Output Card Additions and Upgrades Tool to update your existing output cards and switcher to the new "single-gang" output card format.

Please refer to the DigitalMedia Resources Webpage at http://www.crestron.com/dmresources/ for additional design tools and reference documents.

SPECIFICATIONS

Video

Signal Types: DM 8G® SM Fiber w/Deep Color & 3D, HDMI® w/Deep Color & 3D (DVI compatible [2])

Resolutions, Progressive: 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 852x480@60Hz, 852x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz,



1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50), 1920x1080@60Hz, 2048x1080@24Hz, 2048x1152@60Hz, plus any other resolution allowed by HDMI up to 165MHz pixel clock

Resolutions, Interlaced: 720x480@30Hz (480i), 720x576@25Hz (576i), 1920x1080@25Hz (1080i25), 1920x1080@30Hz (1080i30), plus any other resolution allowed by HDMI up to 165MHz pixel clock

Audio

Signal Types: DM 8G SM Fiber, HDMI

Formats: Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby® TrueHD, DTS®, DTS-ES, DTS 96/24, DTS-HD High Res, DTS-HD Master Audio™, LPCM up to 8 channels

Communications

DigitalMedia: DM 8G SM Fiber, HDCP, EDID, CEC, Ethernet

HDMI: HDCP, EDID, CEC

NOTE: Supports management of HDCP and EDID; supports management of CEC between the connected HDMI device and a control system

Connectors

SMF/LC: (2) LC female optical fiber connectors comprising (2) DM 8G Single-Mode Fiber outputs;

Each connects to the DM 8G SM Fiber input of a DM receiver or other DM device via CresFiber® 8G SM single-mode fiber optic cable [1]

HDMI: (1) 19-pin Type A HDMI, female;

HDMI digital video/audio output, DVI compatible^[2]; Outputs same signal as the left DM 8G SM Fiber output

Indicators

SMF/LC: (2) green LEDs, indicate DM link status for each corresponding DM 8G SM Fiber output



DMC-S20-HD 2-Channel DigitalMedia 8G™ Single-Mode Fiber Output Card for DM® Switchers

Construction

Plug-in card, occupies (1) DM switcher output card slot, includes metal faceplate $\mbox{w/black}$ finish

Weight

6.2 oz (176 g)

MODELS & ACCESSORIES

Available Models

DMC-S20-HD: 2-Channel DigitalMedia 8G[™] Single-Mode Fiber Output Card for DM® Switchers

Available Accessories

CRESFIBER8G-SM-P-SP2KM: CresFiber® 8G Single-Mode Fiber Optic

Cable, plenum, 2 km spool

CRESFIBER8G-SM-CONN-LC-12: Connectors for CresFiber® 8G Single-

Mode Fiber Optic Cable, LC, 12-Pack

CRESFIBER-TK: CresFiber® Termination Kit (AFL Telecommunications®)

CBL Series: Crestron® Certified Interface Cables MP-WP Series: Media Presentation Wall Plates

MPI-WP Series: Media Presentation Wall Plates - International Version

Notes:

- The maximum cable length for DigitalMedia 8G Single-Mode Fiber (DM 8G SM Fiber) is
 7.5 miles (12 km) using Crestron CRESFIBER8G-SM or third-party G.652.D (or better) single-mode fiber optic cable. Refer to the Crestron DigitalMedia Design Guide, Doc. #4546 for complete system design guidelines. All wire and cables are sold separately.
- DVI is supported via the HDMI output using a suitable adapter or interface cable. CBL-HD-DVI interface cables are available separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, CresFiber, DigitalMedia, DigitalMedia 8G, DM, and DM 8G are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby and Dolby Digital are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS-HD, and DTS-HD Master Audio are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDMI is either a trademark or registered trademark of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2015 Crestron Electronics, Inc.