

- Volume of 4.6 cubic feet, holds (147) 12 oz cans or (93) 12 oz bottles
- Energy Star rated
- Holds milk gallons
- Signature SAPPHIRE blue interior
- Full wrapped stainless-steel exterior
- 2 Full-extension stainless steel lined drawers
- Multifunction capacitative touch electronic control
- Temperature range: 34 °F to 65 °F
- Fan-assisted cooling system allows for even temperatures, quicker cooldown times, and added efficiency
- Full LED theater lighting
- Adaptable stainless steel dividers in each drawer allows customization of drawer space
- Stainless model includes 1" diameter stainless steel handles with faceted standoffs (22" length)
- Panel ready model requires ¾" custom door panel and handle
- 4 Independent adaptable leveling legs
- Adaptable grille accepts an integrated toe kick and allows front/back and up/down alignment with adjacent cabinetry and toe kick/plinth
- Automatic defrost
- Lock standard on stainless model



Model Details

Model	Lock	Finish	Description	Shipping Weight
SRD24SS	Yes	Stainless Steel	24" Indoor Refrigerator Drawers, Factory Installed Lock	157 lbs
SRD24PR	No	Panel Ready	24" Indoor Refrigerator Drawers	154 lbs

Dimensions/Weight	Detail
Product Depth	23 ¼"
Product Height	34" - 35"
Product Width	23 %"
Product Weight	127 lbs
Product Volume	4.6 cu ft
Shipping Dimensions	26 ¾" x 27 ½" x 36 ¾"
Shipping Weight	157 lbs

Integration/Panel Information*	Detail
Panel Height	2 Panels: 14 %" each
Panel Thickness	3/4"
Panel Width	23 %"
Maximum Panel Weight	25 lbs

^{*}Refer to manual for all panel and installation instructions









The Legacy Companies warrants to the original purchaser of its SAPPHIRE products that they will be free from defects in materials and workmanship for the following time periods from the date of purchase shown on the sales receipt:





Model	Details
Control Type	Electronic Capacitative Touch with OLED Screen
Indoor or Outdoor	Indoor
Built-in Installation	Inset, Frameless / Overlay and Framed Cabinet Styles
Refrigerant Type	R600a

Electrical	Details
Electrical Requirements	115 V / 60 Hz
Volt Range	104 V ~ 127 V
Electrical Service	15 amp
Running Amps	0.7 amps


Approvals - Certifications	Details
ETL Residential / Commercial	Yes
ETL Sanitation	Yes
Star K	Yes

Capacities	Details
Maximum Shelf Weight	110 lbs
12 oz Can Capacity	147 Cans (Max)
12 oz Bottle Capacity	93 Bottles (Max)





*Dimensions are the same for Panel Ready unit when ¾" panel applied



The Legacy Companies warrants to the original purchaser of its SAPPHIRE products that they will be free from defects in $materials \ and \ workmanship \ for \ the \ following \ time \ periods \ from \ the \ date \ of \ purchase \ shown \ on \ the \ sales \ receipt:$