

DGC 6700-1

Steam oven with full-fledged oven function and XL cavity combines two cooking techniques - steam and convection.



- Perfect results thanks to MultiSteam technology
- Sets new standards regarding brilliance and user convenience -MTouch
- Custom and precise temperature control - cooking with roast probe
- Very convenient water container is behind motorized fascia panel
- Plenty of space to be creative the XL cooking compartment

E	EAN:	400	2515	5646052 /	material	number:	10256750
	_						

Construction type	
Combination steam oven	•
Design	
ContourLine	•
Appliance color	Clean Touch Steel
Control panel	M Touch
Convenience features	
Electronic temperature control of oven in °F	85-435
Electronic temperature control of steam oven in °F	105-212
External steam generation	•
Climate sensor	•
Individual humidity settings in combination cooking	•
Menu cooking without transfer of taste	•
Roast probe	•
Keep-warm function	•
Automatic programs with individual setting of the cooking	•
result Operating modes	
Defrost	•
	More than 200
MasterChef automatic programs Combi cooking	Note than 200
<u>_</u>	•
Steam cooking	
Sous-vide Published	- -
Reheating	<u>•</u>
Broil	
Convection Bake	
Intensive bake	· -
Cake plus	· <u>•</u>
Surround	<u>•</u>
Browning	•
Bake	•
Convection Broil	•
Special modes	•



DGC 6700-1

Steam oven with full-fledged oven function and XL cavity combines two cooking techniques - steam and convection.



Control panel	
MultiLingua	•
MyMiele	•
Show me how	•
Search function automatic programs	•
Steam cooking on up to 3 levels at the same time	•
Motorized lift-up fascia	•
Automatic menu cooking	•
Quantity-independent cooking	•
Steam reduction before end of program	•
Polyphonic acoustic signals	•
Time of day display	•
Polyphonic acoustic signals	•
Date display	•
Minute minder	•
Time buffer in h	200
Start-stop programming	•
Automatic switch-off	•
Actual temperature display	•
Acoustic signal when desired temperature is reached	•
Favorites	20
Sabbath program	•
Individual settings	•
Door	
CleanGlass door	•
Door with viewing screen	•
Door with viewing screen Door hinge side	• Bottom
	Bottom
Door hinge side Cavity XL cavity	Bottom
Door hinge side Cavity XL cavity Cavity volume in cu.ft(l)	• Bottom • 1.84 (52)
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity	•
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels	1.84 (52)
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels	1.84 (52)
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean	1.84 (52) • 3
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps	1.84 (52) • 3
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience	1.84 (52) • 3 • •
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience Stainless steel front with Clean Touch Steel surface	1.84 (52) • 3 • •
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience Stainless steel front with Clean Touch Steel surface Cavity with PerfectClean	1.84 (52) 3 double
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience Stainless steel front with Clean Touch Steel surface Cavity with PerfectClean External steam generator	1.84 (52) 3 class of the state of the stat
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience Stainless steel front with Clean Touch Steel surface Cavity with PerfectClean External steam generator Soak program	1.84 (52) 3 double
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience Stainless steel front with Clean Touch Steel surface Cavity with PerfectClean External steam generator Soak program Rinse program	1.84 (52) 3 double
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience Stainless steel front with Clean Touch Steel surface Cavity with PerfectClean External steam generator Soak program Rinse program Cavity drying program	1.84 (52) 1.84 (52) 3 double
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience Stainless steel front with Clean Touch Steel surface Cavity with PerfectClean External steam generator Soak program Rinse program Cavity drying program Quick-release side racks	1.84 (52) 3 double
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience Stainless steel front with Clean Touch Steel surface Cavity with PerfectClean External steam generator Soak program Rinse program Cavity drying program Quick-release side racks Automatic descaling	1.84 (52) 1.84 (52) 3 double
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience Stainless steel front with Clean Touch Steel surface Cavity with PerfectClean External steam generator Soak program Rinse program Cavity drying program Quick-release side racks Automatic descaling Steam technology and water supply	1.84 (52) 1.84 (52) 3 double
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience Stainless steel front with Clean Touch Steel surface Cavity with PerfectClean External steam generator Soak program Rinse program Cavity drying program Quick-release side racks Automatic descaling Steam technology and water supply MultiSteam	1.84 (52) 1.84 (52) 3 continued a second and a second
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience Stainless steel front with Clean Touch Steel surface Cavity with PerfectClean External steam generator Soak program Rinse program Cavity drying program Quick-release side racks Automatic descaling Steam technology and water supply MultiSteam Water reserve for approx. 90 min cooking	• 1.84 (52) • 3 • double • • • • • • • • • • • • • • • • • • •
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience Stainless steel front with Clean Touch Steel surface Cavity with PerfectClean External steam generator Soak program Rinse program Cavity drying program Quick-release side racks Automatic descaling Steam technology and water supply MultiSteam Water reserve for approx. 90 min cooking Lightweight water container	1.84 (52) 1.84 (52) 3 continued a second and a second
Door hinge side Cavity XL cavity Cavity volume in cu.ft(I) PerfectClean stainless steel cavity No. of rack levels Labeling of rack levels Removable side racks with PerfectClean No. of halogen lamps Cleaning convenience Stainless steel front with Clean Touch Steel surface Cavity with PerfectClean External steam generator Soak program Rinse program Cavity drying program Quick-release side racks Automatic descaling Steam technology and water supply MultiSteam Water reserve for approx. 90 min cooking	• 1.84 (52) • 3 • double • • • • • • • • • • • • • • • • • • •

Miele

DGC 6700-1

Steam oven with full-fledged oven function and XL cavity combines two cooking techniques - steam and convection.




Efficiency and sustainability	
Energy-saving lighting circuit	•
Rapid PreHeat	•
Safety	
Appliance cooling system with cool touch front	•
Safety cut-out	•
System lock	•
Vapor cooling system	•
Door contact switch	•
Technical data	
Niche depth in in. (mm)	22 5/8 (572)
Appliance width in in.(mm)	23 1/2 (595)
Appliance height in in.(mm)	18 (456)
Appliance depth in in.(mm)	22 5/8 (573)
Weight in lbs. (kg)	94 (42.2)
Usable voltage range in V	240/208
Fuse rating in A	20
Number of phases	2
Standard accessories	
No. of universal baking trays with PerfectClean	_ 1
Combi rack with PerfectClean	1
Side racks with PerfectClean	•
No. of perforated stainless steel containers	2
No. of unperforated stainless steel containers	_1
Grease filter	•
Connection wire with plug	•
Descaling tablets	•


Míele

DGC 6700-1

Steam oven with full-fledged oven function and XL cavity combines two cooking techniques - steam and convection.







DGC 6000 XL in a floor unit, CLST (Installation drawing) - USA


- * Appliances with glass front

 ** Appliances with metal front
 1) Steam oven
 2) Niche
 3) Pass-through for the power cord
 4) Recommended postiion for electrical Connection
 5) Power cord

DGC 6000 XL in a tall unit, CLST (Installation drawing) - USA

- * Appliances with glass front


 ** Appliances with metal front
 1) Steam oven
 2) Niche
 3) Pass-through for the power cord
 4) Recommended postion for electrical Connection
 5) Power cord



DGC 6000 XL in a tall unit with oven (Installation drawing) - USA $\,$

- * Appliances with glass front

 ** Appliances with metal front
 1) Steam oven
 2) Niche
 3) Pass-through for the power cord
 4) Recommended postiion for electrical Connection
 5) Power cord
 6) Oven




DGC 6000 XL (detailed installation drawing of open control panel) - USA



DGC 6700-1

Steam oven with full-fledged oven function and XL cavity combines two cooking techniques - steam and convection.





DGC 6000 XL (detailed installation ContourLine) - USA

^{*} Appliances with glass front ** Appliances with metal front